Model 4VS

OptiSafe® Heating System



Description:

Eight mini tank (or combination of both) Dual Temperature

Control Dye Heating System. The standard unit consists of FOUR stainless steel quart-sized tanks (vats) in stainless steel housing for durability. The housing is carefully insulated for minimum heat radiation, and maximum thermal insulation. Model 4VS is designed to optimally heat optical lens tinting solutions and other similar materials, with a temperature range from 60° F to 250° F (15.55° C - 121.1° C). The standard four quart unit can hold up to 8 mini-sized vats (optional), allowing flexibility of constructing a heating system that is suitable for your lab. The system is also supplied complete with vats, lids and starter kit for professional lens tinting.

Specifications:

Heating Element: 2 stainless steel 550 Watt

Watt Density of 27 W/sq. in.

Heating Unit:

Power Requirements: 120 VAC, 60 Hz, 3-terminal

electrical outlet 230 VAC, 50 Hz (Optional)

Heating Solutions: Non-combustible, non-toxic,

Heating Medium: OptiSafe H.T.F., 4 Quarts (3.78 Liters)

and non-reactive with stainless steel

Thermostat Range: 60° F to 250° F (15.55 to 121.1°C)

Dimensions: 19.5 x 11 x 9 in. (49.53 x 27.94 x 22.86 cm)

Weight without 28 lbs. (12.7kg)

H. T. F:

Housing: Stainless steel

Insulation: Fiberglass and silicon rubber

Warranty:

One full year warranty parts and labor.

Packaging & Shipping The OptiSafe Heating System 4VS, Item #E315 is packaged in a 27 x20 x11 in. (68.58 x 50.80 x 27.94 cm) craft box. Shipping weight, including 4 quarts (4x946ml) of OptiSafe H.T.F. = 42 lbs. (19.05kg)

> Item# E315 for 120V, 60 Hz. Item# E315-230 for 230V, 50 Hz.



- Uniform temperature
- 4 quart (4x946ml) size standard system holds up to 8 mini tanks (8x473ml)
- Dual stainless steel heating elements
- All stainless steel construction
- Heavy duty. Designed for continuous operation
- Starter kit



Stainless steel quart and mini tanks (vats). Each quart tank can be replaced with two mini tanks.



Thermostat control dial offers accurate adjustment of the temper



Two stainless steel inner tank and two heating elements are compatible with all heating fluids and solutions.



Tinting is simply done by dipping lenses into hot dye solution.





For a Quote or more infomation contact